

Referans Nr.		x L	b	a	e	k	Sıkma Verileri Tightening Data		
	dx						Nm	kN	(g)
1590-0606025		x25	15						8
1590-0606040	M6x6	x40	28	5.7	10	4	17	17	11
1590-0606063		x63	40						15
1590-0808032		x32	22						13
1590-0808050	M8x8	x50	35	7.7	12	6	43	32	16
1590-0808080		x80	50						20
1590-1010040		x40	23						35
1590-1010063	M10x10	x63	45	9.7	15	6	79	51	45
1590-1010080		x80	50						60
1590-1010100		x100	60						70
1590-1012050		x50	35						50
1590-1012063		x63	40						60
1590-1012080		x80	55						65
1590-1012100	M10x12	x100	60	11.7	18	7	79	51	75
1590-1012125		x125	75						90
1590-1012160		x160	90						105
1590-1012200		x200	120						120
1590-1212050		x50	35						65
1590-1212063		x63	40						70
1590-1212080		x80	55						80
1590-1212100	M12x12	x100	65	11.7	18	7	141	74	100
1590-1212125		x125	75						110
1590-1212160		x160	100						140
1590-1212200		x200	120						160
1590-1214050		x50	35						80
1590-1214063		x63	45						90
1590-1214080		x80	55						100
1590-1214100	M12x14	x100	65	13.7	22	8	141	74	110
1590-1214125		x125	75						135
1590-1214160		x160	100						160
1590-1214200		x200	120						180
1590-1416063		x63	45						115
1590-1416080		x80	55						140
1590-1416100		x100	65						160
1590-1416125	M14x16	x125	75	15.7	25	9	223	101	180
1590-1416160		x160	100						220
1590-1416200		x200	120						255
1590-1416250		x250	150						300
1590-1616063		x63	45						140
1590-1616080		x80	55						160
1590-1616100		x100	65						190
1590-1616125	M16x16	x125	85	15.7	25	9	354	138	225
1590-1616160		x160	100						270
1590-1616200		x200	120						315
1590-1616250		x250	150						380
1590-1618063		x63	45						170
1590-1618080		x80	55						185
1590-1618100		x100	65						220
1590-1618125	M16x18	x125	85	17.7	28	10	354	138	245
1590-1618160		x160	100						295
1590-1618200		x200	120						340
1590-1618250		x250	150						405
1590-1820080		x80	55						260
1590-1820100		x100	65						290
1590-1820125		x125	85						340
1590-1820160	M18x20	x160	110	19.7	32	12	474	169	390
1590-1820200		x200	125						455
1590-1820250		x250	150						535
1590-1820315		x315	190						650
1590-2020080		x80	55						300
1590-2020100		x100	65						330
1590-2020125		x125	85						380
1590-2020160	M20x20	x160	110	19.7	32	12	679	215	450
1590-2020200		x200	125						535
1590-2020250		x250	160						635
1590-2020315		x315	190						760
1590-2022080		x80	55						345
1590-2022100		x100	65						380
1590-2022125		x125	85						435
1590-2022160	M20x22	x160	110	21.7	35	14	679	215	500
1590-2022200		x200	125						590
1590-2022250		x250	150						695
1590-2022315		x315	190						820

Referans Nr.		x L	b	a	e	k	Sıkma Verileri Tightening Data		
	dx						Nm	kN	(g)
1590-2224080		x80	55						465
1590-2224100		x100	65						515
1590-2224125		x125	85						580
1590-2224160	M22x24	x160	110	23.7	40	16	903	266	660
1590-2224200		x200	125						775
1590-2224250		x250	150						805
1590-2224315		x315	190						1050
1590-2424100		x100	70						550
1590-2424125		x125	85						630
1590-2424160		x160	110						725
1590-2424200	M24x24	x200	125	23.7	40	16	1163	310	850
1590-2424250		x250	150						990
1590-2424315		x315	190						1180
1590-2424400		x400	240						1410
1590-2428100		x100	70						660
1590-2428125		x125	85						730
1590-2428160		x160	110						820
1590-2428200	M24x28	x200	125	27.7	44	18	1163	310	950
1590-2428250		x250	150						1090
1590-2428315		x315	190						1300
1590-2428400		x400	240						1530
1590-2428500		x500	290						1800
1590-3036125		x125	80						1280
1590-3036160		x160	110						1440
1590-3036200	M30x36	x200	135	35.6	54	22	2258	493	1620
1590-3036250		x250	150						1880
1590-3036315		x315	200						2150
1590-3036500		x500	300						3010
1590-3642160		x160	100						2260
1590-3642250		x250	175						2890
1590-3642400	M36x42	x400	250	41.6	65	26	3953	719	4010
1590-3642600		x600	340						5900
1590-4248160		x160	100						3550
1590-4248250	M42x48	x250	175	47.6	75	30	6337	986	4530
1590-4248400		x400	250						6160

DIN 787
Ürün Nr. 1590 T-Ayaklı Saplama

- Kalite 12.9
- Siyah kaplama

Product Nr. 1590 T-Slot Bolt

- Quality 12.9
- Black coating


Loctite
8150

Not: 150 °C üzerindeki ortamlarda sıkma işlemi yapılırken dişlerin üzerine Loctite 8150 kullanılır.

Note: Environments on the 150 °C when clamping action on the thread Loctite 8150 is used.

